

AMENDMENTS TO THE CLAIMS

1. (Original) A method of providing visual caller identification, comprising the steps of:

saving a plurality of directory numbers;

receiving a call, the call being associated with a directory number;

querying a database for caller identification information associated with the call;

sending the caller identification information to a caller identification device;

comparing the directory number associated with the call with the plurality of directory numbers;

if one of the plurality of directory numbers matches the directory number associated with the call, displaying a first visual identification indicator, and displaying the caller identification information associated with the call;

if one of the plurality of directory numbers does not match the directory number associated with the call, displaying a second visual identification indicator, and displaying the caller identification information associated with the call; and

if no caller identification information associated with the call is obtained during the step of querying a database for caller identification information associated with the call, displaying a third visual identification indicator, and displaying a message that no caller identification information associated with the call is available.

2. (Original) The method of claim 1, wherein displaying a first visual identification indicator, and displaying the caller identification information associated with the call, further includes:

illuminating a first colored light, and

displaying the caller identification information on a readable display screen of the caller identification device.

3. (Original) The method of claim 2, wherein illuminating a first colored light includes, illuminating a green light during displaying the caller identification information.

4. (Original) The method of claim 3, wherein illuminating a first colored light includes, flashing a green light during displaying the caller identification information.

5. (Original) The method of claim 2, wherein displaying a second visual identification indicator, and displaying the caller identification information associated with the call, further includes:

illuminating a second colored light, and

displaying the caller identification information on a readable display screen of the caller identification device.

6. (Original) The method of claim 5, wherein illuminating a second colored light includes, illuminating a yellow light during displaying the caller identification information.

7. (Original) The method of claim 6, wherein illuminating a second colored light includes, flashing a yellow light during displaying the caller identification information.

8. (Original) The method of claim 5, wherein displaying a third visual identification indicator, and displaying a message that no caller identification information associated with the call is available, further includes:

illuminating a third colored light, and

displaying the message on a readable display screen of the caller identification device.

9. (Original) The method of claim 8, wherein illuminating a third colored light includes, illuminating a red light during displaying the message.

10. (Original) The method of claim 9, wherein illuminating a third colored light includes, flashing a red light during displaying the message.

11
Rule 1126
[[12.]] ~~30~~ (Currently Amended) The method of claim 8, wherein displaying a message that no caller identification information associated with the call is available, further includes:

if caller identification information associated with the call is blocked from display, displaying an indication that the call is a private call; and

if caller identification information associated with the call is not located during querying a database for caller identification information associated with the call, displaying an indication that the call is from an unknown calling area.

12
a2
Cont
[[13.]] ~~31~~ (Currently Amended) The method of claim 1, wherein displaying a first visual identification indicator, and displaying the caller identification information associated with the call, further includes:

flashing a light according to a first flashing sequence, and
displaying the caller identification information on a readable display screen of the caller identification device.

13
[[14.]] ~~32~~ (Currently Amended) The method of claim [[13]] ~~31~~, wherein displaying a second visual identification indicator, and displaying the caller identification information associated with the call, further includes:

flashing a light according to a second flashing sequence, and
displaying the caller identification information on a readable display screen of the caller identification device.

14
[[15.]] ~~33~~ (Currently Amended) The method of claim [[14]] ~~32~~, wherein displaying a third visual identification indicator, and displaying a message that no caller identification information associated with the call is available, further includes:

flashing a light according to a third flashing sequence, and
displaying the message on a readable display screen of the caller

identification device.

15
[[16.]] 34.

(Currently Amended) A method of providing visual caller identification in an Advanced Intelligent Network, including a switch, a service control point and a database of caller identification information, wherein the service control point is functionally connected to the switch, and wherein the method comprises the steps of:

receiving a call from a calling party at a calling party switch directed to a called party at a called party switch;

2
cont
sending call information associated with the call to the service control point, the call information including the directory number of the calling party; at the service control point, querying the database of caller identification information for caller identification information associated with the call, ~~and comparing the directory number of the calling party to one or more directory numbers saved by the called party; comparing the directory number of the calling party with the one or more directory numbers saved by the called party;~~

sending the caller identification information to a called party caller identification device via the called party switch, wherein the caller identification device compares the directory number of the calling party with the one or more directory numbers saved by the called party;

if one of the directory numbers saved by the called party matches the directory number of the calling party, displaying a first visual identification indicator, and displaying the caller identification information associated with the call;

if one of the directory numbers saved by the called party does not match the directory number of the calling party, displaying a second visual identification indicator, and displaying the caller identification information associated with the call; and

if no caller identification information associated with the call is obtained during the step of querying the database of caller identification information for caller identification information associated with the call, displaying a third visual identification indicator, and displaying a message that no caller identification information associated with the call is available.

16
[[17.]] ~~35~~. (Currently Amended) The method of claim [[16]] 34, wherein displaying a first visual identification indicator, and displaying the caller identification information associated with the call, further includes:

illuminating a first colored light, and
displaying the caller identification information on a readable display screen of the caller identification device.

17
[[18.]] ~~36~~. (Currently Amended) The method of claim [[17]] 35, wherein illuminating a first colored light includes, illuminating a green light during displaying the caller identification information.

a2
cont
18
[[19.]] ~~37~~. (Currently Amended) The method of claim [[18]] 36, wherein illuminating a first colored light includes, flashing a green light during displaying the caller identification information.

19
[[20.]] ~~38~~. (Currently Amended) The method of claim [[17]] 35, wherein displaying a second visual identification indicator, and displaying the caller identification information associated with the call, further includes:

illuminating a second colored light, and
displaying the caller identification information on a readable display screen of the caller identification device.

20
[[21.]] ~~39~~. (Currently Amended) The method of claim [[20]] 38, wherein illuminating a second colored light includes, illuminating a yellow light during displaying the caller identification information.

21
[[22.]] ~~40~~. (Currently Amended) The method of claim [[21]] 39, wherein illuminating a second colored light includes, flashing a yellow light during displaying the caller identification information.

22

[[23.]] ~~41~~. (Currently Amended) The method of claim [[20]] 38, wherein displaying a third visual identification indicator, and displaying a message that no caller identification information associated with the call is available, further includes:

illuminating a third colored light, and

displaying the message on a readable display screen of the caller identification device.

23

[[24.]] ~~42~~. (Currently Amended) The method of claim [[23]] 41, wherein illuminating a third colored light includes, illuminating a red light during displaying the message.

24

[[25.]] ~~43~~. (Currently Amended) The method of claim [[24]] 42, wherein illuminating a third colored light includes, flashing a red light during displaying the message.

25

[[26.]] ~~44~~. (Currently Amended) The method of claim [[23]] 41, wherein displaying a message that no caller identification information associated with the call is available, further includes:

if caller identification information associated with the call is blocked from display, displaying an indication that the call is a private call; and

if caller identification information associated with the call is not located during querying a database for caller identification information associated with the call, displaying an indication that the call is from an unknown calling area.

26

[[27.]] ~~45~~. (Currently Amended) A system for providing visual caller identification, comprising:

a software module operative

to query a database for caller identification information associated with a call from a calling party to a called party, the call being associated with a directory number;

to send the caller identification information to a caller

to receive the call;
to store a plurality of directory numbers;
to compare the directory number associated with the call with the plurality of directory numbers;

if one of the plurality of directory numbers matches the directory number associated with the call, to display a first visual identification indicator, and to display the caller identification information associated with the call;

if one of the plurality of directory numbers does not match the directory number associated with the call, to display a second visual identification indicator, and to display the caller identification information associated with the call; and

if no caller identification information associated with the call is located during the step of querying a database for caller identification information associated with the call, to display a third visual identification indicator, and to display a message that no caller identification information associated with the call is available.

a²
Cont
27
[[28.]] ~~46.~~ (Currently Amended) A method of providing visual caller identification, comprising the steps of:

receiving a call at a caller identification device; and
projecting information about the call through a projection orifice in the caller identification device and onto a projection surface.

28
[[29.]] ~~47.~~ (Currently Amended) A method of providing visual caller identification, comprising the steps of:

saving a plurality of directory numbers;
saving visual projection information for each of the plurality of directory numbers;

receiving a call at a caller identification device;
querying a database for caller identification information associated with the call;

sending the caller identification information to a caller identification device;

comparing the directory number associated with the call with the plurality of directory numbers;

if one of the plurality of directory numbers matches the directory number associated with the call, projecting the saved projection information associated with the directory number onto a projection surface; and

if one of the plurality of directory numbers does not match the directory number associated with the call, projecting caller identification information associated with the call onto a projection surface.

29

48. (New) A caller identification device, comprising:

circuitry, operative

to receive a call;

to receive caller identification information associated with the call;

to store a plurality of directory numbers;

to compare the directory number associated with the call with the plurality of directory numbers;

if one of the plurality of directory numbers matches the directory number associated with the call, to display a first visual identification indicator, and to display the caller identification information associated with the call;

if one of the plurality of directory numbers does not match the directory number associated with the call, to display a second visual identification indicator, and to display the caller identification information associated with the call; and

if no caller identification information associated with the call is located, to display a third visual identification indicator, and to display a message that no caller identification information associated with the call is available.

30

49. (New) The caller identification device of claim 48, wherein the circuitry comprises a microprocessor and associated programming.

31

50. (New) A method of providing visual caller identification, comprising the steps of:

comparing a directory number associated with a call with a plurality of directory numbers;

if one of the plurality of directory numbers matches the directory number associated with the call, displaying a first visual identification indicator, and displaying the caller identification information associated with the call;

if one of the plurality of directory numbers does not match the directory number associated with the call, displaying a second visual identification indicator, and displaying the caller identification information associated with the call; and

if no caller identification information associated with the call is located, displaying a third visual identification indicator, and displaying a message that no caller identification information associated with the call is available.
